



Delock Adapter HDMI-A male > Displayport 1.2 female white

Description

This adapter by Delock enables the connection of an Displayport monitor to the system via a free HDMI interface. The adapter supports a resolution up to 4K Ultra HD at 30 Hz and is backward compatible to Full-HD 1080p.



24,5 cm

Specification

· Connectors:

Input:

1 x HDMI-A 19 pin male

1 x USB Type-A male (power supply)

Output:

1 x Displayport 20 pin female

- Chipset: STDP2600
- Displayport 1.2 and High Speed HDMI specification
- High Speed HDMI receiver link rate up to 2.97 Gb/s per data pair
- Resolution up to 4Kx2K @ 30 Hz; 1920 x 1080 @ 120 Hz (depending on the system and the connected hardware)
- Supports 3D displays
- Supports Audio 7.1 channel up to 192 kHz sample rate
- Supports HDCP 1.3
- Gold-plated connectors
- · Colour depth:

RGB / YCC (4:4:4) - 16 bit colour

YCC (4:2:2 / 4:2:0) - 16 bit colour

· Power consumption:

operation: ca. 500 mW

standby: ca. 25 mW

- · Colour: white
- · Cable length incl. connectors: ca. 24.5 cm
- · OS independent, no driver installation necessary

System requirements

- A free HDMI-A female
- One free USB-A female
- · Monitor with a free Displayport interface
- One Displayport cable

Package content

- · Adapter HDMI to Displayport
- User manual

Item no. 62496

EAN: 4043619624966

Country of origin: China

Package: Retail Box







Images

