

# Delock USB Type-C™ 3.1 Docking Station HDMI + DP + VGA 1080p, USB Hub and USB PD function

## Description

This docking station by Delock can be connected to a computer with a USB-C™ Alt-Mode or Thunderbolt™ 3 port and provides a variety of interfaces. Three monitors can be operated simultaneously at the DisplayPort, HDMI and VGA outputs, the same image is displayed on all ports. Two built-in USB Type-A ports and one USB Type-C™ port allows the use of peripherals. With a USB-C™ power supply, laptops such as the Macbook or Chromebook can be charged during operation.

[Delock USB Type-C™ 3.1 Docking Station \(Video\)](#)



## Specification

- Connectors:
  - 1 x HDMI-A 19 pin female
  - 1 x DisplayPort 20 pin female
  - 1 x VGA 15 pin female
  - 1 x USB Type-C™ PD female (power supply)
  - 1 x USB Type-C™ female (data transfer)
  - 1 x USB Type-C™ female (connection to host)
  - 2 x USB 3.0 Type-A female
- Chipset: VL101R, VL170, VL813, CH7039
- Resolution up to 1080p @ 60 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Setting: extended, mirrored, primary display
- Output power: 4.5 W per port
- Input power: 1 x USB Type-C™ female max. 60 W
- Colour: black
- Dimensions (LxWxH): ca. 127 x 63 x 14 mm

## System requirements

- Windows 8.1/8.1-64/10/10-64, Windows 10 Mobile, Android ex 6.0, Mac OS ex 10.12
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

## Package content

- USB-C™ docking station
- Cable USB-C™ male to USB-C™ male, length ca. 10 cm
- User manual

## Item no. 87722


EAN: 4043619877225

Country of origin: China

Package: Retail Box



Images



| General                       |   |
|-------------------------------|---|
| Specification:                | DisplayPort 1.1<br>High Speed HDMI  |
| Supported operating system:   | Android 6.0 or above<br>Mac OS 10.12 or above<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Windows 10 Mobile  |
| Interface                     |   |
| Output:                       | 1 x DisplayPort 20 pin female<br>1 x HDMI-A 19 pin female<br>1 x VGA 15 pin female<br>2 x USB 3.0 Type-A female<br>1 x USB Type-C™ female (data transfer) |
| Input:                        | 1 x USB Type-C™ female (power supply)<br>1 x USB Type-C™ male   |
| Technical characteristics     |   |
| Maximum screen resolution:    | 1920 x 1080 @ 60 Hz   |
| Signal transmission:          | video<br>audio  |
| Voltage:                      | USB bus powered<br>1 x USB Type-C™ Power Delivery female (optional for power supply)  |
| Physical characteristics      |   |
| Cable length incl. connector: | 10 cm   |
| Colour:                       | grey / black  |